



RYNAN[®]
PRINTING



R60 & REACH

CONTROLLER

PRINthead

Touch Screen Controller With Multiple Funai TIJ
Print Heads

R60 REACH



TECHNICAL SPECIFICATIONS

Printing Technology	Funai TIJ
Controller Dimensions	305.6x 200.9 x 64.2 mm
Printhead Dimensions	136.2 x 64.6 x 83.1 mm (1 Printhead) 136.2 x 99.5 x 95.5 mm (2 Printheads) 136.2 x 134.4 x 107.9mm (3 Printheads) 136.2 x 166.7 x 120.2 mm (4 Printheads) 136.2 x 145.1 x 251.3 mm (5 Printheads)
Controller Weight	2750g
Print Head Weight	430g
Display	10" LCD Touch Screen
Power Supply	AC 100V-240V, 50/60H, DC 24V 9.2A
Resolutions	Max 300 DPI
Print Speed	Up to 40m/min at 300dpi
Density	3 levels
Throw Distance	5mm

FEATURES

Wide Range Of Print Types	<ul style="list-style-type: none"> Text, Counter Box/Lot Datetime Expiry Date Julian Date Shiftcode Image Database <p>1D & 2D Barcodes (Code 11, Code 39, Code 128, EAN, QR, Datamatrix, GS1 Datamatrix...)</p>
Printable Height	Maximum 76.2mm / 6 heads
External Connections	<ul style="list-style-type: none"> External Sensor, Encoder and Alarm beacon
Template Length	Standard 2m, Support up to 10m
Database	TXT, CSV
Advance Features	<ul style="list-style-type: none"> Free design in template up to 76.2mm (6 head) POD (Print online data) Integrate with other devices (PLC, Camera, Checkweigher...) via RJ45 Real-time Printing WYSIWYG (what you see is what you get) Data upload, Backup & Recovery via USB
Printable Characters	Windows true fonts - Free design in template up to 76.2mm (6 head)
Print Languages	English (default), Vietnamese, Chinese (PRC), Turkish, Korean, Russian, Japanese, Hebrew, Spanish, Thai, Portuguese and Arabic...
System Languages	English (default), German, Vietnamese, Chinese, Korean, Russian, Turkish, Portuguese, Spanish, Polish, Greek and Italian (and others)

REACH PRINthead COMBINATION

Choice of up to 6 independent printheads

