

**Formulating a Greener World®**

# SoluJET® 2707K

Solvent ink for non-porous media



# TECHNICAL DATA SHEET

SoluJET® 2707K black solvent TIJ 2.5 ink is designed for track and trace coding and marking and other high-productivity industrial packaging printing applications.

SoluJET® 2707K ink provides enhanced stability, good adhesion and rub resistance, long decap time, excellent sharpness and barcode readability on semi-porous and non-porous substrates such as metal, PET, PVC, PA, BOPP and foils.

## Technical Specifications

	<b>SoluJET® 2707K Print Cartridge</b>
<b>Ink type</b>	Black dye solvent ink
<b>Print cartridge type</b>	HP 45si
<b>Resolution</b>	Up to 600 dpi, recommended 300 x 300 dpi
<b>Nozzle count</b>	300
<b>Print swath</b>	12.7 mm
<b>Firing voltage</b>	8.6 V
<b>Fire pulse width</b>	2.0 µs
<b>Pulse warming</b>	OFF
<b>Decap time</b>	Up to 1 h
<b>Drying time</b>	1 - 3 s at 300 x 300 dpi
<b>Throw distance</b>	Up to 5 mm
<b>Average delivered ink</b>	36 mL (vertical) and 33 mL (horizontal)
<b>Average drop volume</b>	34 pL
<b>Operating conditions</b>	15 °C to 35 °C, 35% to 80% RH
<b>Shipping / storage temperature</b>	10 °C to 30 °C
<b>Best before</b>	9 months from filling date

## Cartridge Shipping & Storage

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. Horizontal position is recommend.
- Refer to Safety Data Sheet for more information.

## Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

## Ordering Information

<b>Product number</b>	<b>Product description</b>
2707K42A	SoluJET® 2707K Print Cartridge

### MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam

Tel.: +84 294 3846 997 - Fax: +84 294 3846 998

Email: info@mylangroup.com

Website: www.mylangroup.com