

5720K

Solvent ink for penetrable media

TECHNICAL DATA SHEET

The 5720K Black MEK Solvent ink is specifically formulated for use in Funai Zion Cartridges. This advanced ink is engineered to bond with permeable substrates such as polyvinyl chloride, polycarbonate, acrylic coatings, and polyurethane, ensuring durable and long-lasting print quality. The 5720K ink delivers rapid absorption, outstanding scratch resistance, and chemical resistance. Additionally, it offers prolonged decap time and high optical density for ensuring top-notch print quality.

Technical Specifications

Name	5720K Print Cartridge
Ink type	Black solvent dye ink
Print cartridge type	Funai Zion
Resolution	Up to 300 dpi, recommended 300 x 200 dpi
Nozzle count	320
Print swath	13.5 mm
Firing voltage	9.6 V
Pre-fire pulse width	0.8 µs
Delay width	1.2 µs
Main-fire pulse width	1.6 µs
Pulse warming	OFF/ ON 25 °C
Decap time	20 min
Drying time	2 - 3 s at 300 x 200 dpi
Throw distance	Up to 8 mm
Average delivered ink	40 mL (vertical) and 38 mL (horizontal)
Average drop volume	65 µL
Operating conditions	15 °C to 30 °C, 35% to 80% RH
Shipping / storage temperature	15 °C to 30 °C
Best before	6 months from filling date

Cartridge Shipping & Storage

- Store the cartridge in its sealed pouch until time to use.
- Ensure the cartridge is stored with clip securing printhead, NOZZLES DOWN orientation recommended.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use lint-free cloth dampened with ethanol (> 98%) to clean the cartridge printhead. Use of cloth with lint may clog nozzles.
- Hold the cartridge printhead face down, gently press the printhead on the lint-free cloth and allow ink to wick out. Then, carefully wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	Product description
5720K42A	5720K Print Cartridge

RYNAN Technologies Pte Ltd.

60 Paya Lebar Road, #05-57 Paya Lebar Square

Singapore 409051

Website: www.rynanprinting.com - E-mail: info@rynanprinting.com



v1.3